

Peralte d		Peso	Dimensiones						
			b	a	tw	k	tf	Gramil g	Tornillo o MAX
mm	Pulg.	Kg/m	mm	mm	mm	mm	mm	mm	mm
76.2	3	6.1	35.8	31.5	4.3	16	7	24	10
101.6	4	8.04	40.2	35.8	4.8	16	8	25	13
152.4	6	12.2	48.7	43.6	5.1	19	9	29	16
152.4	6	15.63	52	43.6	8	19	9	29	16
152.4	6	19.63	55	43.6	11	19	9	35	16
203.2	8	17.11	57.4	51.8	5.6	21	10	35	19
203.2	8	20.46	60	51.8	8	21	10	35	19
203.2	8	27.9	64	51.8	12	21	10	38	19
254	10	22.8	66.04	60	6.1	22	11	38	19
254	10	37.2	73.3	60	13.36	22	11	40	19
254	10	44.7	77.04	60	17.09	22	11	40	19
304.8	12	30.8	74.73	67.57	7.16	25.5	13	44	19
304.8	12	37.2	77.39	67.6	9.83	25.5	13	50	19
304.8	12	44.7	80.52	67.6	12.95	25.5	13	50	19

Peralte d		Propiedades								
		Peso		Eje X - X			Eje Y - Y			Distancia
mm	Pulg.	Kg/m.	Área cm2	l cm4	r cm	s cm3	l cm4	r cm	s cm3	x cm
76.2	3	6.1	7.68	68.1	2.97	17.9	8.3	1.04	3.4	1.11
101.6	4	8.04	10	157.9	3.97	31.3	13.3	1.18	4.7	1.16
152.4	6	12.2	15.35	541	5.94	71	29.1	1.38	8.2	1.32
152.4	6	15.63	19.81	628.5	5.64	82.5	36.21	1.35	9.34	1.27
154.4	6	19.35	24.58	720.1	5.41	94.5	45.46	1.35	10.65	1.32
203.2	8	17.11	21.61	1344.5	7.89	132.3	55.4	1.6	13	1.47
203.2	8	20.46	25.94	1490.1	7.59	146.6	62.43	1.57	14.09	1.42
203.2	8	27.9	35.42	1818.9	7.16	179	83.25	1.52	16.39	1.45
254.0	10	22.8	28.97	2805.4	9.83	221.2	94.9	1.81	19.01	1.61
254.0	10	37.2	47.42	3796	8.94	298.2	139.85	1.72	24.25	1.57
254.0	10	44.7	56.9	4287.2	8.69	339.2	163.99	1.7	27.04	1.56
304.8	12	30.8	39.29	5369.4	11.71	352.3	161.5	2.03	28.35	1.77
304.8	12	37.2	47.42	5993.7	11.25	394.9	186.05	1.98	30.81	1.71
304.8	12	44.7	56.9	6742.9	10.89	442.4	213.94	1.98	33.76	1.71